

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

1 Product and Company Identification

- **Product identifier**
- **Trade name:** Mousemilk Fuel Treatment
- **Article number:** WWF MFT
- **Relevant identified uses of the substance or mixture and uses advised against**
CHEMICAL FAMILY NAME: Injector/Carburetor Cleaner
PRODUCT USE: Fuel Additive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Worldwide Filter, Inc.
1689 Abram Court
San Leandro, CA 94577 USA
(510) 483-5122
www.mousemilk.com
- **Emergency telephone number:**
(800) 535-5053 Infotrac
Contact No.: 79544

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.



GHS07

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labeling:**

toluene

Distillates (petroleum), hydrotreated light naphthenic

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme**· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *2 Health = *2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

• Dangerous components:

108-88-3	toluene ⚠ H225; ⚠ H361; H373; H304; ⚠ H315; H336	70-90%
67-63-0	Isopropyl alcohol ⚠ H225; ⚠ H319; H336	15-35%
108-10-1	4-methylpentan-2-one ⚠ H225; ⚠ H332; H319; H335	2-12%
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic ⚠ H350	2-12%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Give large amounts of water. If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 3)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

67-63-0 Isopropyl alcohol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 4)

108-10-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI
· Ingredients with biological limit values:	
108-88-3 toluene	
BEI	0.02 mg/L blood prior to last shift of workweek Toluene
	0.03 mg/L urine end of shift Toluene
	0.3 mg/g creatinine urine end of shift o-Cresol with hydrolysis (background)
67-63-0 Isopropyl alcohol	
BEI	40 mg/L urine end of shift at end of workweek Acetone (background, nonspecific)
108-10-1 4-methylpentan-2-one	
BEI	1 mg/L urine end of shift MIBK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Color: Colorless to light amber

· **Odor:** Sweet, pungent

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 111 °C (232 °F)

· **Flash point:** > 4 °C (> 39 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 425 °C (797 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 6)

- Upper:** 12.0 Vol %
- **Vapor pressure @ 20 °C (68 °F):** 29 hPa (22 mm Hg)
 - **Density @ 20 °C (68 °F):** 0.725 g/cm³ (6.05 lbs/gal)
 - **Relative density** Not determined.
 - **Vapour density** Not determined.
 - **Evaporation rate** Not determined.
 - **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
 - **Partition coefficient (n-octanol/water):** Not determined.
 - **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
 - **Solvent content:**
 - Organic solvents:** 94.7 %
 - VOC content:** 94.7 %
 - **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
Carcinogenic.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 7)

- **Carcinogenic categories**

• IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
67-63-0	Isopropyl alcohol	3
• NTP (National Toxicology Program)		
None of the ingredients is listed.		

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
 - **DOT, ADR, IATA**
 - **IMDG**
 - **UN proper shipping name**
 - **DOT**
 - **ADR**
 - **IMDG, IATA**
- UN1993
UN1993
Not Regulated
None
Flammable liquids, n.o.s. (toluene, Isopropanol (Isopropyl alcohol))
UN1993 Flammable liquids, n.o.s. (toluene, Isopropanol (Isopropyl alcohol))
FLAMMABLE LIQUID, N.O.S. (toluene, ISOPROPANOL (ISOPROPYL ALCOHOL))

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 8)

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids.
- **Label** 3

- **ADR**



- **Class** 3 (F1) Flammable liquids
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 33
- **EMS Number:** F-E,S-E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** UN1993, Flammable liquids, n.o.s. (toluene, Isopropanol (Isopropyl alcohol)), 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
67-63-0	Isopropyl alcohol
108-10-1	4-methylpentan-2-one

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 9)

- **Proposition 65**

- **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
----------	----------------------

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

- **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
----------	---------	----

108-10-1	4-methylpentan-2-one	I
----------	----------------------	---

- **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
----------	---------	----

67-63-0	Isopropyl alcohol	A4
---------	-------------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.	
------------------------------------	--

- **OSHA-Ca (Occupational Safety & Health Administration)**

Corrosive to eyes	
-------------------	--

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

toluene

Distillates (petroleum), hydrotreated light naphthenic

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 08/12/2013

Reviewed on 08/12/2013

Trade name: Mousemilk Fuel Treatment

(Contd. of page 10)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

• **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

• *** Data compared to the previous version altered.**

SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)