

Safety Data Sheet

Issue Date: 09-Nov-2016

Revision Date: 14-Sep-2021

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

SDS # WWF-001-EU
Product Name Mouse Milk Penetrating Oil (Green)

Contains Toluene, Methylisobutyl ketone, Petroleum distillates, hydrotreated light naphthenic, Isopropyl Alcohol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Oil Treatment: Rust and corrosion penetrating and prevention

Uses Advised Against May damage some rubber products

1.3. Details of the Supplier of the Safety Data Sheet

Supplier

Worldwide Filter
1689 Abram Court
Box 1758
San Leandro, CA 94577

For further information, please contact

Contact Point Worldwide Filter Phone: 1-510-483-5122
Email Address sales@mousemilk.com

1.4. Emergency telephone number

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1 - (H304)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)

Serious eye damage/eye irritation	Category 2 - (H319)
Carcinogenicity	Category 1B - (H350)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements

Product Identifier

Contains Toluene, Methylisobutyl ketone, Petroleum distillates, hydrotreated light naphthenic, Isopropyl Alcohol



Signal Word

Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H361d - Suspected of damaging the unborn child

H350 - May cause cancer

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P370 + P378 - In case of fire: Use carbon dioxide, dry chemical or foam to extinguish

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P313 - Get medical advice/attention

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P313 - Get medical advice/attention

P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell

2.3. Other Hazards

No information available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 MIXTURES

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Petroleum distillates, hydrotreated light naphthenic	Present	64742-53-6	51	Carc. 1B (H350)	Not determined
Toluene	Present	108-88-3	39	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)	Not determined
Isopropyl Alcohol	Present	67-63-0	6	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	Not determined
Methylisobutyl ketone	Present	108-10-1	4	(EUH066) Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 2 (H225)	Not determined

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Ingestion

IF SWALLOWED: call a poison control center or physician immediately. Do NOT induce vomiting. Give large amounts of water to drink.

4.2. Most Important Symptoms and Effects, Both Acute and Delayed**Symptoms**

Causes serious eye irritation. Causes skin irritation. Can be harmful if ingested. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any Immediate Medical Attention and Special Treatment Needed**Notes to Physician**

Treat symptomatically.

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing Media**Suitable Extinguishing Media**

Carbon dioxide (CO₂). Dry chemical. Alcohol resistant foam.

Unsuitable Extinguishing Media

DO NOT USE WATER.

5.2. Special Hazards Arising from the Substance or Mixture

Highly flammable liquid and vapour. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Container may rupture on heating. See Section 10 for additional information. Take precautionary measures against static discharge.

Hazardous combustion products

Toxic fumes.

5.3. Advice for Firefighters

Wear self contained breathing apparatus for fire fighting if necessary. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures**Personal Precautions**

Use personal protective equipment as required. Keep unprotected persons away.

For Emergency Responders

Use personal protection recommended in Section 8. Follow all fire fighting procedures in Section 5.

6.2. Environmental Precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

6.3. Methods and Material for Containment and Cleaning Up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Place in appropriate containers for disposal. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents.

Prevention of Secondary Hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to Other Sections

See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment. See Section 13: DISPOSAL CONSIDERATIONS.

Section 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Advice on Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapours/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating / lighting / equipment. Use non-sparking tools. Take precautionary measures against static discharges.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Keep away from open flames, hot surfaces and sources of ignition.

7.3. Specific End Use(s)

Specific Use(s)

Oil Treatment: Rust and corrosion penetrating and prevention.

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Exposure Limits

Chemical name	European Union	United Kingdom	France	Spain	Germany
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ Skin	STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 191 mg/m ³	TWA: 20 ppm TWA: 76.8 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³	S* STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm	TWA: 50 ppm TWA: 190 mg/m ³ H*

		Skin		TWA: 192 mg/m ³	
Isopropyl Alcohol 67-63-0	-	STEL: 500 ppm STEL: 1250 mg/m ³ TWA: 400 ppm TWA: 999 mg/m ³	STEL: 400 ppm STEL: 980 mg/m ³	STEL: 400 ppm STEL: 1000 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³
Methylisobutyl ketone 108-10-1	TWA 20 ppm TWA 83 mg/m ³ STEL 50 ppm STEL 208 mg/m ³	STEL: 100 ppm STEL: 416 mg/m ³ TWA: 50 ppm TWA: 208 mg/m ³ Skin	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	STEL: 50 ppm STEL: 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ H*
Chemical name	Italy	Portugal	Netherlands	Finland	Denmark
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ Skin	STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	STEL: 384 mg/m ³ TWA: 150 mg/m ³	TWA: 25 ppm TWA: 81 mg/m ³ STEL: 100 ppm STEL: 380 mg/m ³ Skin	TWA: 25 ppm TWA: 94 mg/m ³ Skin
Isopropyl Alcohol 67-63-0	-	STEL: 400 ppm TWA: 200 ppm	-	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 250 ppm STEL: 620 mg/m ³	TWA: 200 ppm TWA: 490 mg/m ³
Methylisobutyl ketone 108-10-1	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	STEL: 50 ppm STEL: 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	STEL: 208 mg/m ³ TWA: 104 mg/m ³	TWA: 20 ppm TWA: 80 mg/m ³ STEL: 50 ppm STEL: 210 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ Skin
Chemical name	Austria	Switzerland	Poland	Norway	Ireland
Toluene 108-88-3	Skin STEL 100 ppm STEL 380 mg/m ³ TWA: 50 ppm TWA: 190 mg/m ³	Skin STEL: 200 ppm STEL: 760 mg/m ³ TWA: 50 ppm TWA: 190 mg/m ³	STEL: 200 mg/m ³ TWA: 100 mg/m ³	TWA: 25 ppm TWA: 94 mg/m ³ Skin STEL: 37.5 ppm STEL: 141 mg/m ³	TWA: 192 mg/m ³ TWA: 50 ppm STEL: 384 mg/m ³ STEL: 100 ppm Skin
Isopropyl Alcohol 67-63-0	STEL 800 ppm STEL 2000 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³	STEL: 400 ppm STEL: 1000 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³	STEL: 1200 mg/m ³ TWA: 900 mg/m ³	TWA: 100 ppm TWA: 245 mg/m ³ STEL: 150 ppm STEL: 306.25 mg/m ³	TWA: 200 ppm STEL: 400 ppm Skin
Methylisobutyl ketone 108-10-1	Skin STEL 50 ppm STEL 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	Skin STEL: 40 ppm STEL: 164 mg/m ³ TWA: 20 ppm TWA: 82 mg/m ³	STEL: 200 mg/m ³ TWA: 83 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ Skin STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³ Skin

8.2. Exposure Controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

Personal Protective Equipment

Eye/Face Protection

Tightly sealed goggles.

Hand Protection

Wear protective gloves.

Skin and Body Protection

Suitable protective clothing.

Respiratory Protection

Ensure adequate ventilation, especially in confined areas. In case of brief exposure or low pollution, use respiratory filter device. In case of intensive or longer exposure, use self-contained respiratory protective device.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties**Physical state** Liquid**Appearance**

Colourless to light amber liquid

Odour

Sweet Pungent

Colour

Colourless to light amber

Odour Threshold

Not determined

Property
Values**Remarks • Method****pH**

Not determined

Melting point / freezing point

Not determined

Boiling point / boiling range

111 °C / 232 °F

Flash point

>4 °C / >39 °F

Evaporation Rate1.9 g/cm³**Flammability (Solid, Gas)**

Liquide – Sans objet

Flammability Limit in Air

Upper flammability or explosive limits

Not determined

Lower flammability or explosive limits

Not determined

Vapour Pressure

29 hPa

Vapour Density

Not determined

Relative Density

Not determined

Water Solubility

Not determined

Solubility(ies)

Not determined

Partition Coefficient

Not determined

Autoignition temperature

Le produit ne s'enflamme pas spontanément

Decomposition temperature

Not determined

Kinematic viscosity

Not determined

Dynamic Viscosity

Not determined

Explosive Properties

Not determined

Oxidising Properties

Not determined

9.2. Other information**VOC Content (%)**

394 g/L

Section 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Not reactive under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of Hazardous Reactions**Possibility of Hazardous Reactions**

None under normal processing.

10.4. Conditions to Avoid

Keep out of reach of children. Take precautionary measures against static discharges. See Sec. 7 Handling & Storage.

10.5. Incompatible Materials

None known based on information supplied.

10.6. Hazardous Decomposition Products

None under normal use conditions.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute toxicity

Product Information

Inhalation	Harmful if inhaled.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Ingestion	Do not ingest.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	2,434.00 mg/kg
ATEmix (dermal)	8,084.00 mg/kg
ATEmix (inhalation-gas)	745.00 ppm
ATEmix (inhalation-dust/mist)	3.40 mg/L

Unknown Acute Toxicity

- 100 % of the mixture consists of ingredient(s) of unknown toxicity.
- 51 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
- 51 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
- 6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
- 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).
- 0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Isopropyl Alcohol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Methylisobutyl ketone	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Sensitisation	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	May cause cancer.

Chemical name	European Union
Petroleum distillates, hydrotreated light naphthenic	Carc. 1B

Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Symptoms Please see section 4 of this SDS for symptoms.

Aspiration hazard May be fatal if swallowed and enters airways.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated light naphthenic		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Toluene	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Isopropyl Alcohol	1000: 72 h Desmodesmus subspicatus mg/L EC50 1000: 96 h Desmodesmus subspicatus mg/L EC50	11130: 96 h Pimephales promelas mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
Methylisobutyl ketone	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

12.2. Persistence and Degradability

Not determined.

12.3. Bioaccumulative Potential

Chemical name	Partition coefficient
Toluene	2.7
Isopropyl Alcohol	0.05
Methylisobutyl ketone	1.19

12.4. Mobility in Soil

Mobility

Not determined.

12.5. Results of PBT and vPvB Assessment

Not determined.

12.6. Other Adverse Effects

Not determined.

Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste Treatment Methods****Waste from residues/unused products**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION**IMDG**

14.1 UN number	UN1993
14.2 Proper Shipping Name	Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
14.3 Transport hazard class(es)	3
14.4 Packing Group	II

RID

14.1 UN/ID No	UN1993
14.2 Proper Shipping Name	Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
14.3 Transport hazard class(es)	3
14.4 Packing Group	II

ADR

14.1 UN number	UN1993
14.2 Proper Shipping Name	Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
14.3 Transport hazard class(es)	3
14.4 Packing Group	II

IATA

14.1 UN number	UN1993
14.2 Proper Shipping Name	Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
14.3 Transport hazard class(es)	3
14.4 Packing Group	II

Section 15: REGULATORY INFORMATION**15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture**

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number	Title
Toluene 108-88-3	RG 4bis, RG 84	
Isopropyl Alcohol 67-63-0	RG 84	
Methylisobutyl ketone 108-10-1	RG 84	

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/ELINCS	PICCS	ENCS	IECSC	AICS	KECL
Petroleum distillates, hydrotreated light naphthenic 64742-53-6 (51)	X	X	X	X	-	X	X	X
Toluene 108-88-3 (39)	X	X	X	X	X	X	X	X
Isopropyl Alcohol 67-63-0 (6)	X	X	X	X	X	X	X	X
Methylisobutyl ketone 108-10-1 (4)	X	X	X	X	X	X	X	X

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Section 16: OTHER INFORMATION**Full text of H-Statements referred to under section 3**

H332 - Harmful if inhaled

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H361d - Suspected of damaging the unborn child

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure if inhaled

H304 - May be fatal if swallowed and enters airways

H350 - May cause cancer

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend

TWA

TWA (time-weighted average)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

STEL

STEL (Short Term Exposure Limit)

Ceiling

Maximum limit value

*

Skin designation

Classification Procedure

Calculation method

Issue Date: 09-Nov-2016

Revision Date: 14-Sep-2021

Revision Note: Regulatory review.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2015/830

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

End of Safety Data Sheet