

Safety Data Sheet

Issue Date: 09-Nov-2016

Revision Date: 14-Sep-2021

Version 2

1. IDENTIFICATION

Product identifier

Product Name Mouse Milk Penetrating Oil (Green)

Other means of identification

SDS # WWF-001

UN/ID No UN1993

Recommended use of the chemical and restrictions on use

Recommended Use Oil Treatment: Rust and corrosion penetrating and prevention.

Uses Advised Against May damage some rubber products.

Details of the supplier of the safety data sheet

Supplier Address

Worldwide Filter
1689 Abram Court
Box 1758
San Leandro, CA 94577

Emergency telephone number

Company Phone Number 1-510-483-5122

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Colourless to light amber liquid

Physical state Liquid

Odor Sweet Pungent

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3

Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Signal Word
Danger

Hazard statements

- Harmful if inhaled
- Causes skin irritation
- Causes serious eye irritation
- May cause cancer
- Suspected of damaging fertility or the unborn child
- May cause drowsiness or dizziness
- May cause damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
- Highly flammable liquid and vapor



Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Use explosion-proof equipment
- Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name
CAS No
Weight-%

Petroleum distillates, hydrotreated light naphthenic
64742-53-6
50-60

Toluene
108-88-3
30-40

Isopropyl Alcohol
67-63-0
1-10

Methylisobutyl ketone
108-10-1
1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms	Causes serious eye irritation. Causes skin irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be harmful if swallowed. May be harmful in contact with skin. Harmful if inhaled.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Alcohol resistant foam.

Unsuitable Extinguishing Media DO NOT USE WATER.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Container may rupture on heating. See Section 10 for additional information. Take precautionary measures against static discharge.

Hazardous combustion products Toxic fumes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Use personal protective equipment as required. Keep unprotected persons away.
-----------------------------	---

For Emergency Responders Use personal protection recommended in Section 8. Follow all fire fighting procedures in Section 5.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Contain and soak up with inert absorbent material.

Methods for Clean-Up Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable containers for disposal. Place in appropriate containers for disposal. Do not flush with water or aqueous cleansing agents.

Prevention of Secondary Hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ ventilating / lighting / equipment. Use non-sparking tools. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Isopropyl Alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

Methylisobutyl ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	(vacated) STEL: 1225 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
-----------------------------------	-----------------------------	--	---

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly sealed goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Reference Wiley's "Quick Selection Guide to Chemical Protective Clothing". Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance
Colourless to light amber liquid

Odor
Sweet Pungent

Color
Colourless to light amber

Odor Threshold
Not determined

Property Values

Remarks • Method

pH
Not determined

Melting point / freezing point
Not determined

Boiling point / boiling range

111 °C / 231 °F

Flash point

4 °C / 39 °F

Evaporation Rate

1.9 g/cm³

Flammability (Solid, Gas)

Liquid- Not Applicable

Flammability Limit in Air

Upper flammability or explosive limits

Not determined

Lower flammability or explosive limits

Not determined

Vapor Pressure

29 hPa

Vapor Density

Not determined

Relative Density

Not determined

Water Solubility

Not determined

Solubility in other solvents

Not determined

Partition Coefficient

Not determined

Autoignition temperature

Product is not selfigniting

Decomposition temperature

Not determined

Kinematic viscosity

Not determined

Dynamic Viscosity

Not determined

Explosive Properties

Not determined

Oxidizing Properties

Not determined

Other information**VOC Content (%)**

394 g/L

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children. Take precautionary measures against static discharges. See Sec. 7 Handling & Storage.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation. May be harmful in contact with skin.
Inhalation	Harmful if inhaled.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2180 mg/m ³ (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Isopropyl Alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Methylisobutyl ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity May cause cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	A2	Group 1	Known	X
Toluene 108-88-3		Group 3		

Isopropyl Alcohol 67-63-0		Group 3		X
Methylisobutyl ketone 108-10-1	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 3,298.00 mg/kg

Dermal LD50 3,171.00 mg/kg

ATEmix (inhalation-dust/mist) 3.42 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Isopropyl Alcohol	1000: 72 h Desmodesmus	11130: 96 h Pimephales promelas	13299: 48 h Daphnia magna mg/L

67-63-0	subspicatus mg/L EC50 1000: 96 h Desmodemus subspicatus mg/L EC50	mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	EC50
Methylisobutyl ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Toluene 108-88-3	2.7
Isopropyl Alcohol 67-63-0	0.05
Methylisobutyl ketone 108-10-1	1.19

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Methylisobutyl ketone 108-10-1		Included in waste stream: F039		U161

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic	

			hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Toluene 108-88-3	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1993
Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
Hazard class 3
Packing Group II

IATA

UN number UN1993
Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
Transport hazard class(es) 3
Packing Group II

IMDG

UN number UN1993
Proper Shipping Name Flammable liquids, n.o.s. (Toluene, Isopropyl Alcohol)
Transport hazard class(es) 3
Packing Group II
Marine Pollutant Yes

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum distillates, hydrotreated light naphthenic	X	ACTIVE	X	X		X	X	X	X
Toluene	X	ACTIVE	X	X	X	X	X	X	X
Isopropyl Alcohol	X	ACTIVE	X	X	X	X	X	X	X
Methylisobutyl ketone	X	ACTIVE	X	X	X	X	X	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methylisobutyl ketone 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	30-40	1.0
Isopropyl Alcohol - 67-63-0	67-63-0	1-10	1.0
Methylisobutyl ketone - 108-10-1	108-10-1	1-5	0.1

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental
Methylisobutyl ketone - 108-10-1	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		X	
Toluene 108-88-3	X	X	X
Isopropyl Alcohol 67-63-0	X	X	X
Methylisobutyl ketone 108-10-1	X	X	X

16. OTHER INFORMATION

NFPA

Health Hazards

2

Flammability

3

Instability

0

Special Hazards

Not determined

HMIS

Health Hazards

2*

Flammability

3

Physical hazards

0

